

MATERIAL SAFETY DATA SHEET

Warren Unilube, Inc.

Address: 915 E. Jefferson Ave.
West Memphis, AR 72301

Phone: (800) 428-9284

PRODUCT IDENTIFICATION

Trade Name: CarQuest Multi-Purpose EP Grease (816-14)

Date Revised: March 2, 2004

Synonyms/Product Code: N.A.
 Chemical Name: Petroleum Hydrocarbons
 Family Description: A complex combination of petroleum hydrocarbons containing soap and additives.
 DOT Hazard Class: Not Applicable.

NFPA Codes: Health=0, Flammability=1, Reactivity=0

COMPOSITION

Product	CAS Number	Wt%	Occupational Exposure Limits*			Units
			OSHA PEL	ACGIH TLV	Other	
CarQuest Multi-Purpose Grease	Mixture	100	N.A.	N.A.		
<hr/>						
<u>Ingredient(s):</u>						
Petroleum Hydrocarbon Lubricant	N.A.	>93	5	5	10 STEL	mg/m ³ **
Soap and additives	N.A.	<11	N.A.	N.A.		

* = 8-Hr. TWA unless otherwise specified.
 ** = As mineral oil mist
 N.A. = Not Available
 STEL = Short Term Exposure Limit; 15 minutes.
 N.A. = Not Available.

MEMORANDUM FOR THE DIRECTOR

Subject: [Illegible]

Reference is made to [Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

[Illegible]

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point 760 mmHg:	N.A.	Melting Point: 310-320°F
Vapor Pressure mmHg @ 100F:	N.A.	(dropping pt.)
Solubility in H ₂ O%:	Insoluble	Vapor Density (air=1): N.A.
Specific Gravity (H ₂ O):	0.97	pH: N.A.
% Volatile by Volume:	N.A.	Evaporation Rate: N.A.
Viscosity (method, temp):	9.36-12.57 cSt @ 100 °C	Odor: Mild petroleum odor
Appearance:	Red	

N.A. = Not Available

FIRE AND EXPLOSION DATA

Flash Point:	460°F (Cleveland Open Cup)	
Flammable Limits in Air % by Vol.:	Lower: N.A.	Upper: N.A.
Autoignition Temperature:	N.A.	
Extinguishing Media:	Dry chemical, foam, carbon dioxide or water spray.	
Special Fire Fighting Procedure:	Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Firefighters should wear self-contained breathing apparatus.	
Unusual Fire or Explosion Hazard:	Will not flash spontaneously. May ignite if exposed to open flame.	

REACTIVITY DATA

Stability:	Stable
Hazardous Polymerization:	Will not occur.
Conditions to Avoid/Incompatibility:	Strong oxidizing agents, heat, spark, flame and build-up of static electricity.
Hazardous Decomposition Products:	Incomplete combustion can yield carbon monoxide and various hydrocarbons.

HEALTH HAZARD DATA

This product has not been tested as a whole to determine its specific health hazards. The information provided in this section is based on health hazard information on the product components.

Carcinogenicity: NTP: No	IARC Monographs: No	OSHA Regulated: No
Occupational Exposure Limits:	See <u>COMPOSITION</u> section.	

Effects of Overexposure:

Acute:

Eyes:	An irritant, based on health hazard data of components.
Skin:	The primary hazard associated with use of grease is its accidental injection under the skin with a high pressure gun. If injected under the skin, necrosis could occur.
Inhalation:	Due to the low vapor pressure of this product under ambient conditions, inhalation is not normally a problem.
Ingestion:	Ingestion hazards include possible irritation, nausea, or diarrhea.

1914-1915

1915-1916

1916-1917

1917-1918

1918-1919

1919-1920

1920-1921

1921-1922

1922-1923

1923-1924

1924-1925

1925-1926

1926-1927

1927-1928

1928-1929

1929-1930

1930-1931

1931-1932

1932-1933

1933-1934

1934-1935

1935-1936

1936-1937

1937-1938

1938-1939

1939-1940

1940-1941

1941-1942

1942-1943

1943-1944

1944-1945

1945-1946

1946-1947

1947-1948

1948-1949

1949-1950

1950-1951

Chronic: Frequent or prolonged contact may cause skin irritation.

Additional Medical and
Toxicological Information: May aggravate pre-existing dermatitis.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush thoroughly with water for at least 15 minutes, occasionally lifting the lower and upper lids. Get medical attention if redness or irritation occurs.

Skin Contact: Remove contaminated clothing. Wash affected areas with soap and water. If irritation occurs, get medical attention.

Inhalation: Remove to fresh air. Apply artificial respiration if not breathing. Get medical attention.

Ingestion: Do not induce vomiting. If spontaneous vomiting occurs hold the victim's head lower than hips to prevent aspiration.

SPECIAL PROTECTION INFORMATION

Eye Protection: Remove contact lenses and wear chemical safety goggles, safety glasses, or face shield where contact with the product or mist may occur.

Skin Protection: Wear impervious gloves such as nitrile or neoprene or other materials resistant to petroleum oils when contact with skin may occur.

Inhalation: Use approved respiratory protective equipment for situations where exposure to mist may exceed occupational exposure levels.

Ventilation: Provide adequate ventilation to keep mist or vapors below occupational exposure levels, if applicable.

SPILL OR LEAK AND DISPOSAL PROCEDURES

Spill Procedures: Remove sources of heat or ignition, including internal combustion engines and power tools. Remove spilled material and place in containers for disposal. Use approved respirator where occupational exposure limits for oil mist may be exceeded.

Waste Disposal: Dispose through a licensed waste disposal company. Follow federal, state and local regulations.

SPECIAL PRECAUTIONS AND COMMENTS

Storage Requirements: Store in tightly closed containers in a dry, cool place, away from sources of heat, ignition or strong oxidizers. Ground and bond all transfer and storage equipment.

SARA TITLE III INFORMATION

Admission of [illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

Section 311/312 Hazard Categorization

<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	<u>Reactive</u>
	X			

SARA Hazardous Substances

<u>Ingredient</u>	<u>CAS NO.</u>	<u>% WT</u>	<u>Sec 313</u>	<u>Sec 302</u>	<u>RQ, lb</u>	<u>TPQ, lb</u>
None						

- Key: Sec 313 = Toxic Chemicals, Section 313
- Sec 302 = Extremely Hazardous Substances (EHS)
- RQ = Reportable Quantity of EHS
- TPQ = Threshold Planning Quantity of EHS

CALIFORNIA PROPOSITION 65 WARNING

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be found in the petroleum products. Although it is possible to sufficiently refine the petroleum products to remove the potential for cancer, we are advising that one or more of the listed chemicals may be present in some detectable quantities. Read and follow directions and use care when handling these petroleum products.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THIS COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO THE ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABLENESS AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.

1914

1915

1916

1917

1918

1919

1920

1921

1922

1923

1924