Version 6.1		Revision Date 10/01/2023	Print Date 04/01/2024	
SECTION 1. PRODUCT ANI	COMPA	ANY IDENTIFICATION		
Material name	:	ZEP NON-CHLORINATED BRAK 20N14 12CT	E CLEANER LOW VOC	
Material number	:	00000000001047993		
Manufacturer or supplier's details				
Company	:	Zep Inc.		
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137	1	

: Compliance Services - 877-428-9937

Compliance Services - 877-428-9937

877-541-2016 Toll Free - All Calls Recorded

For a Transportation:CHEMTREC: 800-424-9300 - All Calls Recorded.EmergencyIn the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

:

:

SECTION 2. HAZARDS IDENTIFICATION

Emergency telephone numbers

Emergency Overview

For SDS Information

For a Medical Emergency

Telephone

Appearance	Aerosol containing a compressed gas
Colour	clear
Odour	solvent-like

GHS Classification

Flammable aerosols Gases under pressure Skin irritation Eye irritation Specific target organ toxicity - single exposure Aspiration hazard	 Category 1 Compressed gas Category 2 Category 2A Category 3 (Central nervous system) Category 1
GHS label elements	
Hazard pictograms	: Flame Gas cy linder Health hazard Exclamation mark
Signal word	: Danger
Hazard statements	 H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways.

Version 6.1	Revision Date 10/01/2023	Print Date 04/01/2024
		1 IIII Date 04/01/2024
	H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizzin	iess.
Precautionary statements :	 Prevention: P210 Keep away from heat/sparks/opt No smoking. P211 Do not spray on an open flame of P251 Pressurized container: Do not pi use. P261 Avoid breathing dust/ fume/ gas. P264 Wash skin thoroughly after hand P271 Use only outdoors or in a well-we P280 Wear protective gloves/ eye profine Response: P301 + P310 IF SWALLOWED: Imme CENTER/doctor. P302 + P352 IF ON SKIN: Wash with P304 + P340 + P312 IF INHALED: Re and keep comfortable for breathing. C CENTER/doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rin for several minutes. Remove contact I easy to do. Continue rinsing. P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: C attention. P362 Take off contaminated clothing a Storage: P403 + P233 Store in a well-ventilated tightly closed. P410 + P412 Protect from sunlight. Do temperatures exceeding 50 °C/ 122 °F Disposal: P501 Dispose of contents/container in regulation. 	or other ignition source. ierce or burn, even after / mist/ vapours/ spray. lling. entilated area. tection/ face protection. diately call a POISON plenty of soap and water. emove person to fresh air all a POISON se cautiously with water enses, if present and Get medical advice/ Get medical advice/ and wash before reuse. place. Keep container o not expose to =.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

_

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 50 - < 70
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 30 - < 50
carbon dioxide	124-38-9	>= 5 - < 10
heptane	142-82-5	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

Version 6.1

Revision Date 10/01/2023 Print Date 04/01/2024

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. Get medical attention immediately.
lf inhaled	:	Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	:	If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before re-use.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Most important symptoms and effects, both acute and delayed	:	Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.
		Effects are dependent on exposure (dose, concentration, contact time). Aspiration may cause pulmonary oedema and pneumonitis. Causes serious eye irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards. May be fatal if swallowed and enters airways.
Notes to physician	:	Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet

Version 6.1	Revision Date 10/01/2023	Print Date 04/01/2024
Specific hazards during firefighting	: Do not allow run-off from fire fighti courses.	ng to enter drains or water
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	: Use extinguishing measures that a circumstances and the surrounding	
Further information	: Collect contaminated fire extinguis must not be discharged into drains Fire residues and contaminated fir be disposed of in accordance with For safety reasons in case of fire, separately in closed containments Use a water spray to cool fully closed	s. re extinguishing water must local regulations. cans should be stored
Special protective equipment for firefighters	: Wear self-contained breathing app necessary.	paratus for firefighting if

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	:	Sweep up or vacuum up spillage and collect in suitable container for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms.
	Dispose of rinse water in accordance with local and national regulations.
	Always replace cap after use.

Version 6.1	Revision Date 10/01/2023	Print Date 04/01/2024
Conditions for safe storage	: BEWARE: Aerosol is pressurized. I exposure and temperatures over 50 or throw into fire even after use. Do red-hot objects. No smoking. Keep in a dry, cool and well-ventilat Observe label precautions. Electrical installations / working mar the technological safety standards.) °C. Do not open by force not spray on flames or ed place.
Materials to avoid	: Strong oxidizing agents	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0
		PEL	5,000 ppm 9,000 mg/m3	CAL PEL
		STEL	30,000 ppm 54,000 mg/m3	CAL PEL
heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		С	440 ppm 1,800 mg/m3	NIOSH REL

Components with workplace control parameters

Version 6.1	Revision Date 10/01/2023	Print Date 04/01/2024	4
	TWA	500 ppm OSHA Z-1 2,000 mg/m3	ĺ
	TWA	400 ppm OSHA P0 1,600 mg/m3	
	STEL	500 ppm OSHA P0 2,000 mg/m3	
	PEL	400 ppm CAL PEL 1,600 mg/m3	
	STEL	500 ppm CAL PEL 2,000 mg/m3	
	TWA	400 ppm ACGIH	
	STEL	500 ppm ACGIH	

Biological occupational exposure limits

_

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures	•	effective	ventilation	in all	processing areas
Engineering measures	•	Chective	vonthation	in un	processing areas

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection Material Remarks		Protective gloves The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Safety goggles Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Version 6.1	Revision Date 10/01/2023	Print Date 04/01/2024
Appearance	: Aerosol containing a compressed gas	
Colour	: clear	
Odour	: solvent-like	
Odour Threshold	: No data available	
рН	: Not applicable	
Melting point/freezing point	: No data available	
Boiling point	: No data available	
Flash point	: Not applicable	
Evaporation rate	: No data available	
Flammability (solid, gas, liquid)	: Extremely flammable aerosol.	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: No data available	
Density	: 0.728 g/cm3	
Solubility(ies)		
Water solubility	: slightly soluble	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	
Heat of combustion	: 34.35 kJ/g	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition	: Carbon oxides

Version 6.1

Revision Date 10/01/2023

Print Date 04/01/2024

products

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition Symptoms of Overexposure	 None known. Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions. Effects are dependent on exposure (dose, concentration, contact time). Aspiration may cause pulmonary oedema and pneumonitis. Causes serious eye irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards. May be fatal if swallowed and enters airways. Treat symptomatically. Symptoms may be delayed.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Acute toxicity	
Components:	
acetone: Acute oral toxicity	: LD50 Rat: 5,800 mg/kg
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h
	LC50 Rat: 50.1 mg/l
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg
	LD50 Rabbit: > 7,426 mg/kg

Version 6.1

Revision Date 10/01/2023

Print Date 04/01/2024

heptane:

Acute inhalation toxicity : LC

: LC50 Rat: 103 mg/l Exposure time: 4 h

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Version 6.1	Revision Date 10/01/2023	Print Date 04/01/2024
Ecotoxicity		
No data available		
Persistence and degradability		
No data available Bioaccumulative potential		
Product:		
Partition coefficient: n- octanol/water <u>Components:</u> heptane :	: Remarks: No data available	
Partition coefficient: n- octanol/water	: log Pow: 5	
Mobility in soil		
No data available		
Other adverse effects		
No data available <u>Product:</u>		
Regulation	40 CFR Protection of Environme Stratospheric Ozone - CAA Sect Substances	
Remarks	This product neither contains, no with a Class I or Class II ODS as Clean Air Act Section 602 (40 C + B).	s defined by the U.S.
Additional ecological information	: No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Version 6.1

Revision Date 10/01/2023

Print Date 04/01/2024

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids) Gases under pressure Skin corrosion or irritation Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure Aspiration hazard	e)
SARA 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.	

Version 6.1	Revision Date 10/01/2023	Print Date 04/01/2024
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.	
California Prop. 65		
	This product does not contain any California to cause cancer, birth de reproductive harm.	

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 6.1

Revision Date 10/01/2023

Print Date 04/01/2024

Further information

NFPA:



0 = not significant, 1 = Slight,

2 = Moderate, 3 = High


4 = Extreme

HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 =Slight,

- 2 = Moderate, 3 = High
- 4 = Extreme, * = Chronic



Version 6.1

Revision Date 10/01/2023

Print Date 04/01/2024

occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and w ash before reuse. **Storage**: Store in a w ell-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. **Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	6.1
Revision Date:	10/01/2023
Print Date:	04/01/2024

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.